

Datacenter Series

Smarter Infrastructure Solutions

X5-6000 2U FLASH HCI APPLIANCE

X5-2000 2U HYBRID HCI APPLIANCE

X3-6000

X3-2000

9X PERFORMANCE

3x vm density

62%
LOWER
LATENCY

Breakthrough performance, prioritized to power your business.

Pivot3's Acuity hyperconverged software platform overcomes the performance limitations of conventional hyperconverged infrastructure (HCI). Pivot3's innovative, multi-tier architecture with NVMe flash datapath is orchestrated by advanced Quality of Service (QoS) that simplifies performance management and puts an end to resource contention. Now IT can confidently consolidate a broader set of workloads on a single infrastructure platform and deliver guaranteed performance to the applications that power the business.

Increase Application Performance

Pivot 🕄

Pivot3's state-of-the-art, multi-tier storage architecture combines NVMe PCIe flash, SSD, HDD and RAM in each HCI node for faster performance and cost-effective capacity utilization. With the breakthrough performance levels of NVMe flash, the consolidation of latency-sensitive applications on HCI is now a reality. Additionally, Pivot3's distributed scale-out architecture aggregates the capacity, IOPS, bandwidth and cache of each node into highly-available resource pools that deliver maximum storage performance to your applications.

Simplify IT Management

Making performance easy to manage starts with offering five flexible QoS policies that can be assigned to each workload, without having to know exact performance requirements. For recurring business needs (i.e. quarterly reporting and batch processing) policy changes can be easily scheduled to prioritize performance as needed. By automating policy changes, QoS scheduling gives IT the agility to support the business as application priorities and workloads change. In addition to performance QoS policies, data protection QoS policies ensure snapshots are prioritized and automated to align with changing data protection needs.

Exceed User Expectations

High performance storage by itself is not enough – it must be delivered to the most important business applications when it counts. Intelligent prioritization capabilities through Pivot3's advanced QoS policies set minimum levels for IOPS, throughput and response times for each application. Additionally, Service Levels associated with each QoS policy prioritize performance resources accordingly, ensuring mission-critical workloads meet their service levels during periods of resource contention or degraded mode conditions.

Improve Datacenter Efficiency

Pivot3 effectively resolves the tradeoff of capacity utilization for availability inherent in most HCI solutions that rely on replication for data protection. Patented erasure coding provides an optimal combination of efficiency, protection and performance your business needs for uninterrupted operations. Pivot3's distributed scale-out architecture also enables efficient, non-disruptive scalability by pooling all system resources, which expands with each added HCI node to the cluster. This modular approach to linear scalability means you buy only what you need as your business grows.



Pivot3 Hyperconverged Infrastructure

NEXT GENERATION PERFORMANCE


- Multi-tier Architecture
- NVMe Flash Read/Write Cache and Tiering
- QoS Performance Limits
- QoS Service Levels
- Scale-out Architecture

ADVANCED POLICY-BASED MANAGEMENT

- Performance QoS Policies
- Data Protection QoS Policies
- · QoS Policy Scheduler
- QoS Performance Metrics

COMPREHENSIVE DATA SERVICES

- · Patented Erasure Coding
- Snapshots and Clones
- Asynchronous Replication
- Replication to the Cloud
- Application Integration
- Data Reduction/ Thin Provisioning
- External Storage and Server Support
- vSphere Integration (VAAI, PSA, vCenter)
- Phone Home Capability
- HTML5 GUI (vSphere, Standalone)



- PRIORITY-AWARE AUTOMATIC WORKLOAD PRIORITIZATION
- POLICY-BASED ADVANCED QUALITY OF SERVICE
- PERFORMANCE-ARCHITECTED
 NVMe PCIe MULTI-TIER ARCHITECTURE
- EFFICIENT AND SCALABLE SHARED STORAGE POOL

PIVOT3 X-SERIES HCI APPLIANCES

2U Flash	2U Hybrid	1U Flash	1U Hybrid
Pivot (3)	Pivot 3	() ⊗ ^{1,00}	
Model Name			
X5-6500 / X5-6000	X5-2500 / X5-2000	X3-6500/X3-6000	X3-2500 / X3-2000
Max Domain Size	<u>'</u>		
Unlimited	Unlimited	Unlimited	Unlimited
Max Cluster Size			
16 Nodes	12 Nodes	8 Nodes	8 Nodes
CPU Cores			
2 x 20 Core Intel Xeon 6138 <u>or</u> 2 x 12 Core Intel Xeon 5118	2 x 20 Core Intel Xeon 6138 or 2 x 12 Core Intel Xeon 5118	2 x 20 Core Intel Xeon 6138 <u>or</u> 2 x 12 Core Intel Xeon 5118	2 x 10 Core Intel Xeon 4114
RAM			
256, 384, 768, 1536GB	256, 384, 768, 1536GB	192, 384, 768GB	192, 384, 768GB
NVMe Flash Capacity*			
1.92TB <u>or</u> 1.6TB AIC (X5-6500)	3.8TB <u>or</u> 3.2TB AIC (X5-2500)	1.6TB <u>or</u> 960 U.2 (X3-6500)	1.6TB <u>or</u> 960GB U.2 (X3-2500)
Node Capacity in TB			
15.3, 30.7, 61.4TB SSD	12, 24, 48 HDD	7.6, 15.3, 30.7 SSD	8, 16 HDD
Optional GPU			
1x NVIDIA Tesla (M10, M60)	None	None	None
PCoIP Offload			
1x Teradici	None	None	None
Network Interfaces			
x5-6500: 8 x 10GbE (RJ45 <u>or</u> SFP+)	X5-2500: 8 x 10GbE (RJ45 <u>or</u> SFP+)	x3-6500: 8 x 10GbE (RJ45 <u>or</u> SFP+)	X3-2500: 8 × 10GbE (RJ45 <u>or</u> SFP+)
X5-6000: 6 x 10GbE (RJ45 <u>or</u> SFP+)	X5-2000: 6 × 10GbE (RJ45 <u>or</u> SFP+)	x3-6000: 6 x 10GbE (RJ45 <u>or</u> SFP+)	x3-2000: 6 × 10GbE (RJ45 <u>or</u> SFP+)

^{*} Two node types exist for each X-Series appliance, and NVMe Flash capacity may differ between them. Please see Pivot3 Technical Specifications Guide for details.

